

Appl. No. 10/605,650
Amdt. dated July 27, 2006
Reply to Office action of June 30, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1-7 (cancelled).

5

8 (original): A position adjustment device for adjusting a position of a mounting plate having a plurality of through holes relative to a tray of an optical disk drive for preventing an optical disk mounted on the mounting plate from colliding with the tray, the device comprising:
10 a plurality of bases installed on the tray corresponding to the through holes on the mounting plate;
a plurality of screws threaded into the bases through the corresponding through holes to fasten the mounting plate onto the tray; and
a plurality of nuts threaded onto the screws to fasten the screws onto
15 the mounting plate.

9 (original): The device of claim 8, wherein a depth of each of the screws in the corresponding base is set to adjust the relative alignment of the mounting plate and the tray.
20

10 (original): The device of claim 8, wherein each of the bases is a copper pillar with screw threads.

11 (original): The device of claim 10, wherein the copper pillar is a
25 cylinder with an indent at the center of one face, and the screw threads are positioned on an inside wall of the indent.

Appl. No. 10/605,650
Amdt. dated July 27, 2006
Reply to Office action of June 30, 2006

- 12 (original): The device of claim 10, wherein the copper pillar is a hollow cylinder, and the screw threads are positioned on an inside wall of the cylinder.
- 5 13 (original): The device of claim 8 further comprising a plurality of dampers located between the nuts and the mounting plate, and between a head of each of the screws and the mounting plate for preventing the optical disk drive from being affected by vibrations during operation.
- 10 14 (original): The device of claim 13, wherein the dampers are rubber pads.
- 15 15 (original): A mounting structure of an optical disk drive comprising:
a mounting plate comprising a notched base plate;
a tray comprising a base;
a damper installed on the notched base plate; and
a screw, wherein a portion of the screw is threaded into the base, and
the damper elastically connects the mounting plate to the screw;
wherein the screw is capable of being rotated in the base to adjust a
depth of the screw threaded into the base to set a distance between the
20 mounting plate and the tray.
- 25 16 (original): The mounting structure of claim 15, wherein the screw further comprises a shaft and a head, and the mounting structure further comprises a nut, the nut being threaded onto the shaft of the screw so that a predetermined clearance is left between the nut and the head of the screw for installing the damper.
- 17 (original): The mounting structure of claim 15, wherein the base is a

Appl. No. 10/605,650
Amdt. dated July 27, 2006
Reply to Office action of June 30, 2006

copper pillar with an inside circular sidewall, the circular sidewall having screw threads for accepting the screw.

- 5 18 (original): The mounting structure of claim 15, wherein the damper is cylindrical and comprises an upper large diameter portion and a lower large diameter portion, a space between the upper and lower large diameter portions having a smaller diameter for fitting into the notched base plate of the mounting plate.
- 10 19 (original): The mounting structure of claim 15, wherein the screw further comprises a glue layer on the surface of the threads of the screws for fixing the depth of the screw in the base.